

# Adhesives

Our special adhesives are qualified for particular requirements for the surface finishing. All adhesives show excellent processability and good printing properties.

UV adhesives are not suitable for food packaging.

For optimum curing of the UV adhesive a UV unit with a lamp output of minimum 120W/cm is recommended.

Storage	Packaging <sup>1</sup>	Safety data sheet
Storage stability in original packaging when stored between 15° and 25°C is 9-12 months.  Caution: Protect adhesive from direct sunlight.	5 kg Can 10 kg Can 200 kg Drum 600 kg Container	Safety data sheet on request

Product code	Description	Substrate	Application
<b>Adhesive water-based</b>			
9320 PR	Water-based Adhesive	Paper, Film <sup>2</sup>	Good adhesive strength, no yellowing, good resistance to aging, low odour, not flammable.
<b>UV Adhesive</b>			
9308 PR	Adhesive for laminating foil	Film <sup>2</sup>	Adhesive for laminating a wide variety of materials, excellent crosslinking, high adhesive power.
9335 PR	Adhesive for cold foil stamping	Film <sup>2</sup>	Suitable for different cold foil, applicable on all not-absorbant materials, also suitable for finest structures.
9336 PR	Resealable UV Adhesive	Paper, Film <sup>2</sup>	UV Adhesive is suitable to laminate a wide range of materials like HDPE, LDPE, PVC, PET and metal. <u>Viscosity:</u> 100s/ 6mm

<sup>1</sup> Not every product is available in this packaging.

<sup>2</sup> Film: Corona-pretreatment of the substrat is recommended.