

AF Waterlabel Series 14

AF Series 14 is a high pigmented water-based ink for flexo printing, suitable for all papers and topcoat films.

The series has high brilliance and an excellent processability, with excellent runability and ensures a high quality print results with very good dot sharpness.

Storage	Additives	Production
Storage stability in original packaging when stored between 15° and 25°C is 24 months.	9002 AF Retarder 9006 AF Thinner 9240 PR Antifoam 2400 RS Cleaner 2000 RS Cleaner for printing plates	Colour Mixings from PANTONE® or from a colour sample are produced from 5 kg
Packaging	Safety data sheet	Hazardous Substances Statement
5 kg Plastic Can	Safety data sheet on request	See safety data sheet

Product code	Colour								Paper			Film ^{3 + 4}				Thermal Paper ⁵	
		Viscosity 4 mm 20° C	Lightfast ness ¹	Alkali	Acid	Water- resistance	TT ²	Coated	Un coated	Carton	PE	PP	OPP	Metal	Top	Eco	
Process Colours																	
3014 AF	Process Yellow	30s±5	7-8	+	+	+	+	+	+	+	O	O	-	-	+	O	
0104 AF	Process Magenta	20s±5	4-5	O	O	+	+	+	+	+	O	O	-	-	+	O	
2014 AF	Process Cyan	30s±5	8	+	+	+	+	+	+	+	O	O	-	-	+	O	
7014 AF	Process Black	25s±5	8	+	+	+	+	+	+	+	O	O	-	-	+	O	
PANTONE																	
0314 AF	Yellow	30s±5	6	+	+	+	+	+	+	+	O	O	-	-	+	O	
0334 AF	Orange	30s±5	6	+	+	+	+	+	+	+	O	O	-	-	+	O	
0014 AF	Warm Red	30s±5	6-7	+	+	+	+	+	+	+	O	O	-	-	+	O	
0324 AF	Red 032	30s±5	4-5	O	O	+	+	+	+	+	O	O	-	-	+	O	
0024 AF	Rubine Red	20s±5	4-5	+	+	+	+	+	+	+	O	O	-	-	+	O	
0034 AF	Rhodamine	30s±5	3-4	+	+	O	+	+	+	+	O	O	-	-	+	O	

									Paper			Film ^{3 + 4}				Thermal Paper ⁵	
Product code	Colour	Viscosity 4 mm 20° C	Lightfast ness ¹	Alkali	Acid	Water-resistance	TT ²	Coated	Uncoated	Carton	PE	PP	OPP	Metal	Top	Eco	
0114 AF	Purple	30s±5	3-4	+	+	O	+	+	+	+	O	O	-	-	+	O	
1124 AF	Violet	30s±5	6-7	+	+	O	+	+	+	+	O	O	-	-	+	O	
0724 AF	Blue 072	25s±5	6-7	+	+	+	+	+	+	+	O	O	-	-	+	O	
0214 AF	Reflex Blue	25s±5	6-7	+	+	+	+	+	+	+	O	O	-	-	+	O	
0224 AF	Process Blue	30s±5	8	+	+	+	+	+	+	+	O	O	-	-	+	O	
0514 AF	Green	30s±5	8	+	+	+	+	+	+	+	O	O	-	-	+	O	
0714 AF	Black	30s±5	8	+	+	+	+	+	+	+	O	O	-	-	+	O	
0614 AF	Transp. White	35s±5		+	+	+	+	+	+	+	O	O	-	-	+	O	
6614 AF	Covering White	25s±5		+	+	+	+	+	+	+	O	O	-	-	+	O	

¹ Outdoor use can reduce the lightfastness.² Suitability for hot stamping and printing with thermal transfer tapes should be tested under realistic conditions.³ Corona-pretreatment of the substrate is recommended.⁴ For printing on films our Polylabel-Series is recommended.⁵ For printing on thermal paper our Thermolabel-Series is recommended.

The information contained in this leaflet are intended as guidelines. They are based on experience after thorough testings in the laboratory and testings under realistic conditions. The contents are not legally binding.

Pantone® is a registered trademark of Pantone Inc.

+ very good suitable O limited suitable - not suitable

Stand: November 2015